



AirMax – PTMP Solution Setup

- AP Side Setup:
 - Mode: AP/WDS
 - Channel Width: 20MHz or below
 - Data Rates: Best/Auto
 - Security: WPA/WPA2
 - AirMax: AirMax On
 - NoACK: OFF
 - AutoACK: On



AirMax – PTMP Solution Setup

- Station Side Setup:
 - Mode: STA/WDS
 - Channel Width: Match with AP
 - Data Rates: Best/Auto
 - Security: WPA/WPA2
 - AirMax: AirMax On
 - NoACK: OFF
 - AutoACK: On
 - AirMax Priority: Set per client requirements

AirMax – PTP Solution Setup



17km or less

- AP Side Setup:
 - Mode: AP/WDS
 - Channel Width: 40MHz
 - Data Rates: Best/Auto
 - Security: WPA/WPA2
 - AirMax: AirMax On
 - NoACK: OFF
 - AutoACK: On

AirMax – PTP Solution Setup



17km or less

- Station Side Setup:
 - Mode: STA/WDS
 - Channel Width: Match with AP
 - Data Rates: Best/Auto
 - Security: WPA/WPA2
 - AirMax: AirMax On
 - NoACK: OFF
 - AutoACK: On

AirMax – PTP Solution Setup



17km or more

- AP Side Setup:
 - Mode: AP/WDS
 - Channel Width: 40MHz
 - Data Rates: Best/Auto
 - Security: WPA/WPA2
 - AirMax: AirMax On
 - NoACK: ON
 - AutoACK: This option is not valid with NoACK ON

AirMax – PTP Solution Setup



17km or more

- Station Side Setup:
 - Mode: STA/WDS
 - Channel Width: Match with AP
 - Data Rates: Best/Auto
 - Security: WPA/WPA2
 - AirMax: AirMax On
 - NoACK: ON
 - AutoACK: This option is not valid with NoACK ON