



Ubiquiti Inc.
685 Third Avenue
New York, NY 10017
USA

The information in this document applies to the following products **UA-Electric Lock, UA-Magnetic Lock 280kg, UA-Magnetic Lock 500kg**

Hereby declares under our sole responsibility that the **products listed above**, to which this declaration relates, is in conformance with the provisions of Directives

1. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4):

- Shown on carton label

2. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

- Door use, fire resistant, and mild corrosion resistance

3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

- Ubiquiti Inc.
685 Third Avenue, 27th Floor New York, New York 10017
Tel:+1 408-942-3085

4. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):

- Ubiquiti Inc.
685 Third Avenue, 27th Floor New York, New York 10017
Tel:+1 408-942-3085

5. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:

- System 3

6. In case of the declaration of performance concerning a construction product covered by a harmonized standard:

- The certificates are issued by NB 1282 with the below certificate number by a harmonized standard, EN 1155:1997+A1:2002+AC:2006.

| Product Model | Certificate Number |
|------------------------|---------------------------|
| UA-Electric Lock | 1282-5M210204.UOC16 |
| UA-Magnetic Lock 280kg | 1282-5M210204.UOC17 |
| UA-Magnetic Lock 500kg | 1282-5M210204.UOC18 |



7. Declared performance:

| Essential characteristics | Performance | Harmonized technical specification |
|-----------------------------|---|------------------------------------|
| Category of use | Grade 3, for doors for use by the public | EN 1155:1997+A1:2002+AC:2006 |
| Durability | Grade 5, 50 000 test cycles | |
| Hold-open power size | Grade 4~6 | |
| Fire/smoke compartmentation | Grade 1, suitable for use on fire/smoke door assemblies | |
| Safety | Grade 1, pass | |
| Corrosion resistance | Grade 1, mild resistance | |
| Dangerous substances | None | |

8. The performance of the product identified in point 1 is in conformity with the declared performance in point 7. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Mark Feil
Compliance Manager

New York
March 9, 2021