

Switch Lite 8 PoE





Mechanical

| Dimensions | 99.6 x 163.7 x 31.7 mm (3.92 x 6.44 x 1.25") |
|------------|--|
| Weight | 295 g (10.4 oz) |

Hardware

| Total non-blocking line rate | 8 Gbps |
|---|------------------------------------|
| Max. power consumption | 8W |
| Power method | 54V DC, 1.1A power adapter |
| Power supply | External 54V/60W power adapter |
| Supported voltage range | 50-57V DC |
| Networking interface | (8) 10/100/1000 MbE RJ45 ports |
| PoE interface | (4) PoE/PoE+ (Pins 1, 2+; 3, 6-) |
| | |
| Management interface | Ethernet In-Band |
| Management interface Max. PoE+ wattage per port by PSE | Ethernet In-Band 30W |
| | |
| Max. PoE+ wattage per port by PSE | 30W |
| Max. PoE+ wattage per port by PSE PoE budget | 30W 52W |
| Max. PoE+ wattage per port by PSE PoE budget Modes | 30W 52W SMB layer 2 PoE GbE switch |

LEDs

| System | (1) Power: blue/white Flashing white: bootup in progress Flashing blue: firmware upgrading Steady white: factory defaults, awaiting adoption Steady blue: device is adopted |
|----------|---|
| Ethernet | Green: 1G Amber: 10/100 Mbps |
| PoE | Amber: PoE/PoE+ |

