




PicoStation2

Limitless Applications

Pico2 DATASHEET



SYSTEM INFORMATION							
Processor Specs	Atheros MIPS 4KC, 180MHz						
Memory Information	32MB SDRAM, 8MB Flash						
Networking Interface	1 X 10/100 BASE-TX (Cat. 5, RJ-45) Ethernet Interface						
REGULATORY / COMPLIANCE INFORMATION							
Wireless Approvals	FCC Part 15.247, IC RS210, CE						
RoHS Compliance	YES						
RADIO OPERATING FREQUENCY 2412-2462 MHz							
TX SPECIFICATIONS			RX SPECIFICATIONS				
	DataRate	TX Power	Tolerance		DataRate	Sensitivity	Tolerance
802.11b	1Mbps	20 dBm	+/-1dB	802.11b	1Mbps	-95 dBm	+/-1dB
	2Mbps	20 dBm	+/-1dB		2Mbps	-94 dBm	+/-1dB
	5.5Mbps	20 dBm	+/-1dB		5.5Mbps	-93 dBm	+/-1dB
	11Mbps	20 dBm	+/-1dB		11Mbps	-90 dBm	+/-1dB
802.11g OFDM	6Mbps	20 dBm	+/-1dB	802.11g OFDM	6Mbps	-92 dBm	+/-1dB
	9Mbps	20 dBm	+/-1dB		9Mbps	-91 dBm	+/-1dB
	12Mbps	20 dBm	+/-1dB		12Mbps	-89 dBm	+/-1dB
	18Mbps	20 dBm	+/-1dB		18Mbps	-88 dBm	+/-1dB
	24Mbps	20 dBm	+/-1dB		24Mbps	-84 dBm	+/-1dB
	36Mbps	18 dBm	+/-1dB		36Mbps	-81 dBm	+/-1dB
	48Mbps	16 dBm	+/-1dB		48Mbps	-75 dBm	+/-1dB
	54Mbps	15 dBm	+/-1dB		54Mbps	-72 dBm	+/-1dB
ADJUSTABLE CHANNEL SIZE SUPPORT							
5MHz		10MHz		20MHz			
ANTENNA & RANGE PERFORMANCE							
RP-SMA Antenna Included	Outdoor Omni-directional. 6dBi (U.S.), 0dBi (EU Version)						
Indoor/Outdoor Range	Over 50m / 150m						
PHYSICAL / ELECTRICAL / ENVIRONMENTAL							
Enclosure Size	13.6 cm. length x 2.0 cm. height x 3.9cm. width						
Weight	0.10kg						
Enclosure Characteristics	Outdoor UV Stabilized Plastic						
Max Power Consumption	4 Watts						
Power Rating	12V, 1A (12 Watts). Supply and injector included						
Power Method	Passive Power over Ethernet (pairs 4,5+; 7,8 return)						
Operating Temperature	-20C to +70C						
Operating Humidity	5 to 95% Condensing						
Shock and Vibration	ETSI300-019-1.4						
SOFTWARE							
							
visit www.ubnt.com/airos							

